

ArcticChill 98

Direct Chill Cooler

- Chiller capacity: 30 - 40 ltrs of below 12°C chilled water/hour
- Ambient capacity: virtually unlimited
- Can be fitted with drip tray overflow kits & mains drainage
- Fits our standard cowl and wall bracket
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height

23cm Dispensing
Height To Fill
Bottles

The ArcticChill 98
Direct Chill Cooler
With Ambient
Water



ArcticChill 98 KLARAN
The Klaran UVC LED Shield
Is Situated Between The
Direct Chill Tank & In Front
Of The Dispensing Tap

ArcticChill 98 KLARAN

Direct Chill Cooler Plus KLARAN UVC LED Purification System

- The Klaran UVC LED Shield is designed to destroy bacteria and viruses to protect your health
- The KLARAN UVC LED Shield represents a major technological break-through by providing 24/7 protection against bacterial contamination
- The revolutionary KLARAN UVC LED Shield destroys 99%+ of Cryptosporidium, Giardia, E-Coli, Pseudomonas, Legionella and other bacteria
- The Klaran UVC LED Shield is situated between the Direct Chill Tank and in front of the dispensing tap, to provide point of dispense protection from bacteria and viruses

AAFIRST
WATER COOLERS
& BOILERS



refreshingly different

ArcticChill 98 & ArcticChill 98 KLARAN

Direct Chill Cooler Plus KLARAN UVC LED Purification System



Key Feature

First Select Ambient Or Cold, Then Hold The Dispensing Button Down

Accessories For The ArcticChill 98

Installation Rail With Filter. Includes Compression Fitting, 1-Micron Green Filter, Water Block, Copper Pressure Reducing Valve & Non-Return Valve



FloodGuard - Closed Inlet Solenoid Only Opens To Allow Water Into The Cooler, When Water Is Dispensed. By Remaining Closed All Other Times It Protects The Cooler Against Leaks



Filter Housing With Carbon Block Candle & Nanofilter



Mains Drainage - Connect The Drip Tray To Mains Drainage. Can Be Supplied With A Pump, To Pump The Water Over 50m & A Rise Of 5m



Cowling To Fix The Cooler Securely To The Wall (Supplied Separately)



10 Litre Overflow System With Alarm To Signal When Full. (Factory Fitted)



KLARAN UVC LED SHIELD

For Direct Chill/ Ice Bank Coolers

- The KLARAN UVC LED Shield represents a major technological break-through by providing 24/7 protection against bacterial contamination
- The revolutionary KLARAN UVC LED Shield destroys 99%+ of Cryptosporidium, Giardia, E-Coli, Pseudomonas, Legionella and other bacteria
- Simple to install and maintenance free, which is in stark contrast to conventional UV light systems, the KLARAN UVC LED Shield adds real value to your water cooler offer
- KLARAN UVC LED Shield can be supplied factory installed into an AA Water Cooler, or can be provided as a unit for self-installation



A Pumped Main Drainage System Pumps The Waste Water From The Drip Tray Over A Distance Of 100m & A Rise Of 5m. (Factory Installed)



3 Litre Overflow Kit Connects The Drip Tray To A 3 Litre Alarmed Overflow Container. The Container Has A Tap To Empty Without Removing It



Description	Hourly Output		Temp	Dimensions H X W X D (mm)	Weight (Kg)
	Chilled	Ambient			
POU Floor Standing	30-40 Ltrs/Hr	Indefinite	Below 12C	1135 x 340 x 340	25

AAFIRST
WATER COOLERS
& BOILERS

www.aafirst.co.uk